

电蒸汽锅炉技术参数表

项目		蒸汽发生器				蒸汽锅炉											
		LDR0.03	LDR0.05	LDR0.06	LDR0.07	LDR0.05	LDR0.1	LDR0.2		LDR0.3		LDR0.5		WDR1	WDR1.5	WDR2	
额定蒸发量	kg/h	30	50	65	75	50	100	200		300		500		1000	1500	2000	
额定工作压力	mPa	0.4/0.7				0.7	0.7	0.7	1	0.7	1	0.7	1	1	1	1	1
额定蒸汽温度	℃	151/170				170	170	170	184	170	184	170	184	184	184	184	184
额定电功率	kW	24	36	48	54	36	72	144		216		360		720	1080	1440	
加热管组数*功率	组*kW	2*12	2*18	2*18+12	3*18	2*18	4*18	6*24		9*24		12*30		24*30	36*30	48*30	
给水温度	℃	20															
设计热效率	%	98															
水容量	L	23	27	29.6	29.6	48.5	49.5	270		350	350	690	690	1500	2500	2500	
运输重量	T	0.09	0.18	0.19	0.2	0.18	0.21	0.3	0.4	0.35	0.52	0.58	0.65	1.6	2.1	2.4	

电蒸汽锅炉安装尺寸表

项目	压力表管座	给水管座	主蒸汽管座	副蒸汽管座	安全阀管座	排污管座	外形尺寸					
	DN	DN	DN	DN	DN	DN	L	L1	W	W1	H	H1
LDR0.03	15(1/2")	15(1/2")	15(1/2")	/	20(3/4")	20(3/4")	410	/	650	/	960	/
LDR0.05	15(1/2")	15(1/2")	15(1/2")	/	20(3/4")	20(3/4")	660	/	680	/	1190	/
LDR0.06	15(1/2")	15(1/2")	15(1/2")	/	20(3/4")	20(3/4")	660	/	680	/	1190	/
LDR0.07	15(1/2")	15(1/2")	15(1/2")	/	20(3/4")	20(3/4")	660	/	680	/	1190	/
LDR0.1	15(1/2")	15(1/2")	20(3/4")	/	20(3/4")	25	870	800	765	700	1190	1450
LDR0.2-0.7	15(1/2")	20(3/4")	32	/	40(1 1/2")	25	870	840	1000	950	1430	1780
LDR0.2-1.0	15	25	32	/	40	25	890	840	1000	950	1430	1780
LDR0.3-0.7	15(1/2")	25	40	/	40	25	880	830	710	670	1810	2150
LDR0.3-1.0	20	25	40	/	40	25	880	830	710	670	1810	2150
LDR0.5-0.7	20(3/4")	40	40	/	40	40	1200	1100	980	940	1935	2250
LDR0.5-1.0	20	40	40	/	40	40	1200	1100	980	940	1935	2250
WDR1	20	40	50	/	40	40	2380	1960	1700	900	1800	2150
WDR1.5	20	40	65	/	2*40	40	2670	2160	1900	900	2040	2250
WDR2	20	40	80	25	2*40	40	3400	2960	1850	900	1870	2250

